



BRONTO SKYLIFT
S 70 XR 220
 Extendable platform
 200 ... 600 kg

600 kg
 360 kg
 200 kg

R020239A

TECHNICAL DATA	
Safe working load max.	: 600 kg
Max. permitted wind speed	: 12.5 m/s
Typical GVW	: 32 ton
min. operating weight	: 31.3 ton
Outrigger width and length c/c	
- normal jacking	: 8.0/6.5 m
- one side jacking	: 5.6.2/6.5 m
- narrow jacking	: 3.2/6.5 m
Calculation code	:

EU

PRELIMINARY

All rights reserved
 This specification may be revised without notice.
 This document, which is our exclusive intellectual property, shall be treated as strictly private and confidential and shall neither be copied nor communicated to any third person without our written consent.
 BRONTO SKYLIFT OY AB
 Tampere Finland

ULOTTUVUUSKAAVIO
 RÄCKVIDSDIAGRAM
 OUTREACH DIAGRAM
 ARBEITSDIAGRAM
 DIAGRAMA DE TRABAJO

SYSTEM Vertex G4	Massa kg	Las	Pun	Yleistoleranssit Koneistus : SFS4011 Keski Meisto : SFS4012 Levy- ja Hitsustyöt: BBS 2.51
	Suunnittelija RKe		2017-10-20	
	Hyväksyjä			
Mittakaava 1 : 225	Arkkikoko A2	Status		



Piirustus nro. R020239A Rev.

Nimitys
 Ulottumakaavio, S 70 XR, 200-360-600 kg
 +/- 220 asteen korinkääntö, Levitettävä

Rev.	Muutosno.	Muutos	Pvm	Muut.